

Del Mar Sediment Management Study



March 22, 2018

Lindsey Sheehan

Sediment Management Plan

- Why develop this plan?
 - Vulnerability Assessment identified risks with sea-level rise
 - Beach erosion → coastal flooding
 - Channel deposition → increased river flooding

Sediment Management Plan

- Why develop this plan?
 - Vulnerability Assessment identified risks with sea-level rise
 - Beach erosion → coastal flooding
 - Channel deposition → increased river flooding
- What is the purpose of the plan?
 - Understand sediment dynamics to inform dredging and nourishment to reduce risks
 - Companion document to Adaptation Plan and LCP Amendment

Sediment Management Plan

- **Why develop this plan?**
 - Vulnerability Assessment identified risks with sea-level rise
 - Beach erosion → coastal flooding
 - Channel deposition → increased river flooding
- **What is the purpose of the plan?**
 - Understand sediment dynamics to inform dredging and nourishment to reduce risks
 - Companion document to Adaptation Plan and LCP Amendment
- **How was the plan developed?**
 - Gathered data to develop long-term sediment budget
 - Developed existing conditions budget
 - Considered how each process will change with sea-level rise
 - →Developed Channel Dredging Plan
 - →Developed Beach Nourishment Plan
 - →Developed planning-level cost estimates with assumptions

What is a Sediment Budget?

Coastal management tool to understand balance between sediment added and removed from a coastal system



Sediment Budget “Boxes” to Understand Current Processes



Sediment Budget “Boxes” to Understand Current Processes




Sediment Budget “Boxes” to Understand Current Processes



Sediment Budget “Boxes” to Understand Current Processes



Sediment Budget “Boxes” to Understand Current Processes



Longshore Transport

- Many studies analyzing longshore transport in the region
 - Marine Advisers 1960
 - Hales 1978
 - Inman and Jenkins 1983
 - Tekmarine Inc 1987
 - Moffatt and Nichol 1990
 - USACE 1991
 - Inman and Masters 1991
 - Coastal Environments 2001
 - Patsch and Griggs 2006
- ESA also modeled transport rates near Del Mar
- Results vary, because longshore transport is variable
- Typically, transport is to north in the summer, to the south in the winter
- Generally, results show net transport to the south

Beach Nourishment

- Sand bypassing from lagoons
 - About 21,900 cy/yr from San Elijo
 - About 9,500 cy/yr from San Dieguito

Beach Nourishment

- Sand bypassing from lagoons
 - About 21,900 cy/yr from San Elijo
 - About 9,500 cy/yr from San Dieguito
- Regional Beach Sand Project (RBSP) through SANDAG

Location	RBSP I, 2001		RBSP II, 2012	
	Volume (cy)	Grain Size (mm)	Volume (cy)	Grain Size (mm)
Moonlight Beach	105,000	0.34 – 0.62	92,000	0.48
Cardiff Beach	101,000	0.34	89,000	0.57
Fletcher Cove	146,000	0.14	142,000	0.55
Del Mar	183,000	0.14	n/a	n/a
Torrey Pines	245,000	0.14	n/a	n/a

Beach Nourishment

- Sand bypassing from lagoons
 - About 21,900 cy/yr from San Elijo
 - About 9,500 cy/yr from San Dieguito
- Regional Beach Sand Project (RBSP) through SANDAG

	RBSP I, 2001		RBSP II, 2012	
Location	Volume (cy)	Grain Size (mm)	Volume (cy)	Grain Size (mm)
Moonlight Beach	105,000	0.34 – 0.62	92,000	0.48
Cardiff Beach	101,000	0.34	89,000	0.57
Fletcher Cove	146,000	0.14	142,000	0.55
Del Mar	183,000	0.14	n/a	n/a
Torrey Pines	245,000	0.14	n/a	n/a

- Opportunistic sand placement

Beach Dynamics- the Beach “Box”

- Alongshore transport into box
- Dredging and bypassing
- Bluff/gully erosion
- Beach dynamics
 - Shoreline change
 - Beach transect volume change
- Influence of lagoon (lagoon box)



SANDAG Beach Transects

- Fall and spring surveys
- 1997 to present
- 7 transects between San Elijo & San Dieguito
- 4 transects between San Dieguito & Los Peñasquitos




SANDAG Beach Transects

- In 1997, US Navy Homeporting project added 170,000 cy of sand



Feet Above Average Daily Lowest Tide Water Level (e.g., ft MLLW)




SANDAG Beach Transects

- RBSP I (2001) eroded away in the following years



Feet Above Average Daily Lowest Tide Water Level (e.g., ft MLLW)




SANDAG Beach Transects

- RBSP II (2012) transported to 25th St by 2015



Feet Above Average Daily Lowest Tide Water Level (e.g., ft MLLW)







SANDAG Beach Transects

- Before and after 2015-2016 El Niño




Feet Above Average Daily Lowest Tide Water Level (e.g., ft MLLW)







Placed Volume (cy/LF)

Placed Volume (cy/LF)





Existing Conditions Beach Dynamics - Findings

- During 2002-2012 time period Del Mar Beach eroded, even with bypassing from San Dieguito Lagoon
 - Losing 7,900 cy/yr from beach
 - Already nourishing with 9,500 cy/yr from San Dieguito dredging/bypassing
 - Beach needs 17,400 cy/yr to remain stable

Lagoon Dynamics- the Lagoon “Box”

- River/lagoon input
- Dredging and bypassing
- Lagoon mouth dynamics
 - Quantified Conceptual Model (QCM)





Quantified Conceptual Model (QCM)


**Coastal
Forcing**

**Inlet/Beach
Morphology**

**Lagoon
Hydrology**



Existing Conditions (2016) Model Output



Existing Conditions Lagoon Dynamics

- **Waves bring sand into mouth**
 - Builds flood shoal
 - Raises elevation of bottom of channel (or thalweg)
- **Tides move sand out of mouth and limit shoal**
 - More water moving causes scouring of mouth
- **Dredging creates a hole, which fills rapidly at first, and then flattens out**

Future Conditions


- Looked at how each input and output would change with higher ocean water levels
- Helps project how beach and inlet mouth conditions may change

Future Longshore Transport

- Existing longshore transport is highly variable and will be in the future too
- Considerations for transport in the future:
 - Increased storminess could increase transport rates
 - Erosion of beaches to the north and south could mean there is less or no sand to transport, lowering transport rates


Future Beach Dynamics

Current conditions at Del Mar Beach




- Existing beach profile

Beach Dynamics with Sea-Level Rise



- Profile shifts up and in with sea-level rise (Bruun rule)

Beach Dynamics with Sea-Level Rise






- Nourishment needs to raise entire profile to keep pace with sea-level rise

Beach Nourishment - Findings

- From existing conditions, need 17,400 cy/yr to maintain beach width for entire Del Mar under current conditions
- With future sea-level rise, additional nourishment need:

	1 ft of SLR	2 ft of SLR	5.5 ft of SLR
Current need	17,400 cy/yr	17,400 cy/yr	17,400 cy/yr
Additional need with SLR	34,000 – 35,600 cy/yr	50,900 – 53,200 cy/yr	76,400 – 80,200 cy/yr
Total nourishment	51,400 – 53,000 cy/yr	68,300 – 70,600 cy/yr	93,800 – 97,600 cy/yr

Lagoon Mouth Dynamics with Sea-Level Rise



Larger tidal prism scours thalweg, prevents closure

Lagoon Dynamics with Sea-Level Rise- Findings

- Mouth may stay open without dredging
- Bed level predicted to increase with sea-level rise as assumed for Vulnerability Assessment
- Adaptation, for example mouth dredging, would be needed to reduce projected increase in flood risk as identified in Adaptation Plan
 - Mouth dredging volume would need to increase in order to maintain existing level of flood risk
 - Increased dredging volume is small compared to volume needed for beach nourishment

Sediment Budget Findings, compared to RBSP

	RBSP I	RBSP II	Average
	2001	2012	~Every 11 years
Del Mar	183,000	-	n/a
Solana Beach	146,000	142,000	144,000
Cardiff Beach	101,000	89,000	95,000
Oceanside Littoral Cell	1,833,000	1,082,000	1,457,500
Total for SANDAG RSBP	2,104,000	1,532,000	1,818,000

	Current	1 ft of SLR	2 ft of SLR	5.5 ft of SLR
Nourishment needed every 11 years	191,400 cy	374,000 – 391,000 cy	559,000 – 585,000 cy	840,000 – 882,000 cy

Conclusions & Recommendations

- Current San Dieguito Lagoon mouth dredging program not expected to maintain walkable beach with sea-level rise
- To keep up with sea-level rise, would need to place ~1M cy of sand every ~10 yrs (at 5 ft of sea-level rise)
 - Cost \$21m - \$22M per nourishment event
 - Feasibility uncertain at higher sea-level rise amounts (e.g., > 2 - 3ft)
 - Estimates assume neighboring cities nourish at a similar scale, otherwise sand would be lost to neighbors
 - Sand retention structures would be needed if neighbors don't nourish at same level to make nourishment effective
 - At this scale, might not be feasible due to availability of and competition for sand sources
 - Would still require higher sea walls

Conclusions & Recommendations

- Coordinated regional sediment management with beach targets is recommended
 - Sand placed directly on beach has better potential to maintain walkable beach than relying on up-coast nourishment
 - Consider participating in future SANDAG program with some optimization for Del Mar beaches
- There are approaches for strategic placements (timing, grain size, etc.) that could improve effectiveness
- Sand placement may have some negative impacts
 - Beach ecology, sand mining impacts, increase lagoon mouth deposition and maintenance
- Sand retention structures could increase effectiveness
 - Artificial reefs are recommend for consideration as a potential multi-benefit approach and potential effectiveness in trapping sand due to high rates of both north and south transport

Channel Dredging Plan

- **Existing Conditions**
 - Possible sand deposition upstream of railroad → Data gap
 - More monitoring needed to understand deposition
- **Near-term Recommendations**
 - Monitor channel deposition upstream of railroad
 - Evaluate flood risks
 - Increasing mouth dredging could reduce sand depositing further in
 - Dredging upstream of railroad as needed, but more difficult, costly
- **Long-term Recommendations**
 - Increased deposition likely with up to 2 ft of sea-level rise
 - → Increased flood risk
 - Frequent downstream dredging (below railroad) will become less effective and dredging upstream of railroad regularly may be infeasible
 - Likely that other adaptation measures will become necessary

Beach Nourishment Plan

- **Near-term Recommendations**
 - 17,400 CY/yr needed for Del Mar beaches under current conditions (more than currently receiving)
 - Place sand strategically (wave forecasting, etc.)
 - Increase frequency of SCE dredging (permit allows as frequently as every 8 months)
 - Monitoring- review SANDAG data regularly
 - Other current/future projects in the area

Beach Nourishment Plan

- **Long-term Recommendations**
 - Lagoon dredging alone not sufficient to maintain beach
 - Larger-scale placements, similar to RBSP I and II needed
 - Regional coordination recommended
 - Sand retention structures such as offshore reefs
 - Sand supply/sources
 - Offshore (like RBSP I and II)
 - Opportunistic nourishment- City could set up Sand Compatibility and Opportunistic Use Program
 - Lake Hodges reservoir

Questions?

